AVAILABLE COLOURS



MATTE AXIS GRAY METALLIC



IMPERIAL RED METALLIC









SUNSET BROWN METALLIC

TECHNICAL SPECIFICATION+

BODY DIMENSIONS	
Length	2020 mm
Width	738 mm
Height	1099 mm
Wheel Base	1285 mm
Ground Clearance	180 mm
Kerb Weight	111kg (disc)
Fuel Tank Capacity	8.5L
ENGINE	
Emission Standard	BS-IV
Туре	Air Cooled, 4 Stroke, SI Engine
Displacement	109.19 сс
Max Net Power	6.20 kW (8.31 bhp) @7500 rpm
Max Net Torque	9.09 Nm @ 5000 rpm
Bore	50.0 mm
Stroke	55.6 mm
Compression Ratio	9.9:1
Air Filter Type	Viscous Paper Filter
Starting Method	Kick/Self
TRANSMISSION	
No of Gears	4
Gear Pattern	N-1-2-3-4
Max Speed	86 Kmph*
TYRES & BRAKES	
Tyre Size (Front)	80/100-18
Tyre Size (Rear)	80/100-18
Tyre Type (Front)	Tubeless
Tyre Type (Rear)	Tubeless
Brake Type & Size (Front)	Drum 130 mm/ Disc 240 mm
Brake Type & Size (Rear)	Drum 130 mm
FRAME & SUSPENSION	
Frame Type	Diamond
Front	Telescopic Fork
Rear	Spring Loaded Hydraulic
ELECTRICALS	
Battery	12V 3Ah (MF)
Headlamp	12V 35/35W

1. New Livo meets Bharat Stage IV norms. 2. ⁺The technical specifications and design of the motorcycles shown here may vary according to the requirements and conditions and are subject to change without any notice. 3. Accessories shown in the picture are not a part of the standard equipment. 4. *Achieved under Honda test conditions. 5. **Conditions apply.















EDGY FRONT LOOK

Always arrive in style with

unique combination of

sharp headlight &

detailed air duct design.



DYNAMIC GRAPHICS

Curved tank with aggressive shroud & 3D wing mark makes you the centre of



ENTICING MUFFLER
Two piece modern design
muffler makes you irresistible
for a second look.



eave a strong & lasting impression with fresh design of tail light & grab



Provides comfortable ride on all types of

LOW ROLLING
RESITANCE TYRE Honda patented low rolling resistance tyre which increase fuel efficiency.



MF BATTERY & VISCOUS

Have peace of mind as less maintenance is required by MF battery & viscous filter.

With dynamic new graphics, stunning design and digital analogue meter with service due indicator.



IIITY REIII

HET WITH BS-IV
The Honda Eco Technology (HET)
equipped Livo is now meeting the latest emission norms.



SEAL CHAIN
Increases the chain life by 1.6 times.
Reduces the customer stress for maintenance.

