

BULLET 350 KS

TECHNICAL SPECIFICATIONS



ENGINE

Type	Single cylinder 4 stroke, air cooled fuel injection
Displacement	346cc
Bore x stroke	70 mm x 90 mm
Compression ratio	8.5 : 1
Maximum power	19.1 bhp @ 5250 rpm
Maximum torque	28 Nm @ 4000 rpm
Ignition system	Electronic ignition ECU/Variable
Clutch	Wet multiplate (6 plates)
Gearbox	Constant mesh, 5 speed
Lubrication	Wet sump
Engine oil	SAE 15W 50 API SL Grade & Above JASO MA2 Semi Synthetic
Fuel supply	Electronic fuel injection
Air cleaner	Paper element
Engine start	Kick Start

CHASSIS & SUSPENSION

Type	Single downtube, using engine as stressed member
Front suspension	Telescopic, 35 mm forks, 130 mm travel
Rear suspension	Twin shock absorbers with 5 step adjustable preload, 80 mm travel

DIMENSIONS

Wheelbase	1395 mm
Ground clearance	135 mm
Length	2170 mm
Width	810 mm (without mirrors)
Seat Height *	800 mm
Height	1120 mm (without mirrors)
Kerb weight	186 kg (with 90% fuel and oil)
Fuel capacity	13.5 ltr

BRAKES & TYRES

Tyres front	3.25 X 19" - 54P
Tyres rear	3.25 X 19" - 60P
Brakes front	280 mm disc, 2-Piston caliper with ABS
Brakes rear	153 mm Drum, Single Lead Internal Expanding
ABS	Single Channel (Front Brake)

ELECTRICALS

Electrical system	12 volt - DC
Battery	12 V - 8 Ah VRLA
Head lamp	12V, HSI-35/35 W Halogen
Tail lamp	12V, 21W/5W
Turn signal lamp	12V, 10W X 4 Nos.

COLOURS

Seat Height * - Measured Value



Black



Onyx Black



Forest green



Bullet Silver