











The truly Zyada Ka Fayda scooter now comes with **ETFi** (Eco Thrust Fuel injection), a new age fuel injection technology optimized for better economy and performance.

The TVS Jupiter's refined engine delivers enhanced mileage, better rideability and durability for your vehicle and a superior riding experience to you – all adding to the overall ownership experience of the TVS Jupiter.

## **ETFI BENEFITS**

**Enhanced mileage 15**%\* better fuel economy.

**Improved driveability** Smooth power delivery with jerk-free riding.

**Smoother engine refinement** Smooth & consistent engine idling.

Easy maintenance Timely diagnosis due to OBD (On-board diagnostics) keeps maintenance cost low.

**Hassle-free startability** At all operating conditions.

**Superior durability** *Effective component protection at all operating conditions lead to durability.* 

## ZYADA CONVENIENCE

True to the promise of offering 'zyada', the new TVS Jupiter comes with thoughtfully designed features ensuring ease of use and convenience.





## ZYADA COMFORT

Every feature in the new TVS Jupiter is ergonomically designed for better rideability keeping in mind the comfort of the rider and his family.





FRONT TELESCOPIC SUSPENSION



LARGE FRONT & REAR ALLOY WHEELS

# ZYADA SAFETY

The safety features of the new TVS Jupiter are tailored to keep the rider secure irrespective of changing conditions .



SYNC BRAKING TECHNOLOGY





# ZYADA STYLE

The new TVS Jupiter strikes a balance between style and substance with unique features that gives you the element of style with each ride.







# ZYADA COLOURS

#### **TVS JUPITER**



### **TVS JUPITER ZX**



### TVS JUPITER CLASSIC







## **SPECIFICATIONS**

**ENGINE (BS-VI compliant)** 

Single cylinder, 4 stroke, CVTi, fuel injection Туре

109.7cc

Displacement Bore x Stroke 53.5 x 48.8 mm Air Filter Type Viscous paper filter Maximum Power 5.5 kW @ 7000 rpm Maximum Torque 8.4 Nm @ 5500 rpm Transmission Type CVT automatic

Starting System Kick and electric starter

**ELECTRICALS** 

ECU Controlled ignition Ianition Battery 12V, 4Ah MF battery

Head Lamp & Tail Lamp LED

**CHASSIS & SUSPENSION** 

Frame High rigidity underbone type 1834 x 678 x 1286 mm Dimensions (lxbxh)

Wheelbase 1275 mm

Ground Clearance 150 mm (unladen)

Kerb Weight 109 kg Wheels Allov

Front Suspension Telescopic hydraulic

3 step adjustable type coil spring with Rear Suspension

hydraulic damper

**BRAKES & TYRES** 

Front & Rear Ø130 mm Drum (SBT) Tyre Size (Front & Rear) 90/90-12 54 J (tubeless)











