



The call of the BLUE

60th WORLD GP YAMAHA ANNIVERSARY



1960



1970



1980



2010

R15M

ABS
DUAL CHANNEL

QUICK SHIFTER
Standard for R15M & Racing Blue color

TRACTION CONTROL SYSTEM

ASC
ASSIST & SLIPPER CLUTCH

VVA
VARIABLE VALVE ACTUATION

UPSIDE DOWN FRONT FORKS

NOW WITH **CONNECT**



S P E C I F I C A T I O N S



Engine

Engine type	Liquid cooled, 4-stroke, SOHC, 4-valve
Displacement	155 cc
Bore x stroke	58.0 x 58.7 mm
Compression ratio	11.6:1
Maximum horse power	13.5kW(18.4PS)/10000r/min
Maximum torque	14.2N·m(1.4kgf·m)/7500r/min
Fuel system	Fuel injection
Clutch type	Wet, multiple-disc
Starting system type	Electric starter
Transmission type	Constant mesh, 6-speed

Chassis

Frame type	Deltabox
Front suspension system	Telescopic Upside Down Fork (USD Fork)
Rear suspension system	Linked-Type Monocross Suspension
Brake type (front)	Disc brake (282 mm)
Brake type (rear)	Disc brake (220 mm)
Tyre size (front)	100/80-17M/C 52P Tubeless
Tyre size (rear)	140/70R-17M/C 66H Radial Tubeless
Inner tube diameter of front fork	37.0 mm
ABS	Dual channel

Dimensions

Overall length	1990 mm
Overall width	725 mm
Overall height	1135 mm
Seat height	815 mm
Wheelbase	1325 mm
Minimum ground clearance	170 mm
Kerb weight (with oil and a full fuel tank)	142 kg
Fuel tank capacity	11 l

Other Information

Battery	12 V, 4 Ah
Headlight	Bi-functional LED (Class D)
Position light	LED
Brake/tail light	LED
Speedometer	Digital
Tachometer	Digital
Fuel meter	Digital
Shift timing light	Equipped
VVA	Equipped
VVA indicator	Equipped
Quick shifter indicator	Equipped
Fuel consumption indicator	Equipped
Gear position indicator	Equipped
Clock	Digital, auto adjust with smartphone connectivity
Riding Modes	Track Mode / Street Mode
Dual horn	Equipped
Y-Connect (Smartphone Bluetooth Connectivity)	Equipped
Side stand engine cut-off switch	Equipped
Traction control system	Equipped
Quick shifter (up-shift)	Standard for R15M & Racing Blue color



Authorised Dealer

The specifications and designs of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colors shown may not match the actual color due to printing limitations. *Conditions apply. **Warranty extended for engine, FI system, AIS system and Electricals including wiring harness, whichever is earlier. 5-Year warranty* only applicable in case of purchase of Yamaha Protection Plus Policy during validity period. Please refer to Yamaha Protection Plus Policy for more details.

Yamaha Motor India Sales Pvt. Ltd., AKDR Tower-5th Floor, Door No. 3/381, Rajiv Gandhi Salai (OMR) Mettukuppam, Chennai - 600097. Phone: 044-3814 7000. Toll Free No.: 1800 420 1600 Email: info@yamaha-motor-india.com www.yamaha-motor-india.com